Anchor systems

Serie KA



Ball anchor: the steel ball anchor is turned from solid material and forms a homogeneous unit with the high-performance magnet. The adhesive surface is ground, the magnetic core is protected against corrosion and damage.

The KA series is also optionally available with a rubber jacket.

Also available - rubber sleeve for various load levels:

KA-13GM (Rubber sleeve for ball anchors 1,3t)

KA-25GM (Rubber sleeve for ball anchors 2,5t)

KA-50GM (Rubber sleeve for ball anchors 5,0t)

KA-75GM (Rubber sleeve for ball anchors 7,5t)

KA-100GM* (Rubber sleeve for ball anchors 10,0t)

*on demand

sku	Höhe (mm)	Durchmesser (mm)	load_level	Haftkraft (kp)
KA-13DM	27,0	60,0	1.3	170,0
KA-25DM	33,0	74,0	2.5	265,0
KA-50DM	42,0	94,0	5.0	470,0
KA-75DM	53,0	118,0	7.5/10	600,0
GU-KA13	34,0	69,0	1.3	110,0
GU-KA25	38,0	82,0	2.5	185,0
GU-KA50	42,0	95,0	5.0	160,0
KA-13GM				
KA-25GM				
KA-50GM				

MTK Magnet-Fabrik Solingen GmbH | Dycker Feld 21 | 42653 Solingen
Fon: + 49 (0)212 64 59 88 - 0 | Fax: + 49 (0)212 64 59 88 - 31 | E-Mail: info@mtk-magnetfabrik.de